

Husqvarna T 10000

T 10000 is an effective industrial dust extractor to match the highly productive Dual Drive Technology™ grinding machines Husqvarna PG 820 RC, PG 820, PG 680 RC, PG 680 as well as shavers, shot blasters and saws. Also perfect together with our pre separator C 5500 that easily can be mounted on the dust extractor. T 10000 is ideal for heavy-duty work and exacting demands on dust extraction. Powerful motor with ample capacity. The machine can deal with materials that are difficult to handle, such as grinding dust and demolition materials in a wide variety of applications. Has a reliable filter system with high collecting efficiency and a long filter life, and can deal with large quantities of fine dust. Equipped with three tested and certified HEPA class H13 filters ensuring clean air exhaust. The primary sock-style pre-filters provide long, uninterrupted service and can be cleaned efficiently from outside the tank via Jet Pulse air pressure. The Longopac® bag hose system ensures simple, dust-free bag changes.



Durable design

Corrosion-resistant steel clamps, welded frame with dust bag platform and durable steel handle make it ready to serve for many years.



Easy and efficient filter cleaning

The Jet Pulse filter cleaning system ensures high continuous airflow thanks to easy and efficient cleaning of the conical main filter without opening the machine.

Efficient filtration system

The three separate filtering stages result in longer working time between filter cleaning. The dust is filtered through a cyclone chamber, which separate the heaviest parts, up to 95% of the dust, before the washable main filter. The HEPA micro filters are individual tested and certified to capture 99.99% of the remaining silica dust in the respirable fraction (0.3µm).



Excellent stability and mobility

The slim design, solid non-marking tires, swivel casters and hitch for attaching a separator allows for excellent mobility and stability.



FEATURES

- Efficient filtration system
- Easy and efficient filter cleaning
- Durable design
- Excellent stability and mobility
- High Efficiency Particulate Air filter
- Easy-to-read airflow monitoring
- Clean and simple bag change
- For demanding industrial applications
- Control

Technical Specifications	
MOTOR	
Phases	3~
Voltage	400 V
Max. vacuum	300 mbar
Rated input power	11 kW
Product size height	1727 mm
Product size length	1400 mm
Product size width	736 mm
Weight	336 kg
SPECIFICATIONS	
Air Flow	900 m³/h
HEPA filters 99.99% at 0.3 microns	3
Max. vacuum	300 mbar
Water lift	118 in
PACKAGING	
Packaging length	2030 mm
Packaging width	1400 mm
Packaging height	800 mm
Packaging volume	2273.6 dm³

ACCESSORIES



HUSQVARNA C 5500
967 66 46-01



HUSQVARNA PG 820 RC
967 30 29-01



HUSQVARNA PG 820
965 19 56-07



HUSQVARNA PG 680 RC
967 62 27-01



HUSQVARNA PG 680
965 19 57-07



HUSQVARNA PG 530
965 19 58-06



HUSQVARNA PG 530
965 19 58-07



HUSQVARNA PG 530
965 19 58-08



HUSQVARNA PG 530
965 19 58-10



HUSQVARNA PG 530
965 19 58-11



HUSQVARNA PG 530
965 19 58-12



VACUUM TRAILER
590 43 33-01



PIPE
590 43 65-01

ADAPTOR
590 42 93-01



ADAPTOR
590 42 87-01

HOSE ASSEMBLY
590 42 81-01



RUBBER BLADE
590 42 85-03



FLOOR TOOL
590 42 83-02



PRE-FILTER
590 43 86-01



HOSE ASSEMBLY
590 43 70-01



DUST BAG
590 42 92-01



HEPA FILTER
590 42 97-01