DKS15.1 DIAMOND CORE DRILL



- Nominal power: 2000 W
- Drilling diameter: 30 – 180 mm
- Number of gears: 2
- Dry drilling machine with soft impact
- with aluminium housing

Powerful dry drilling machine with soft impact, 2-speed gearbox with oil bath lubrication and overload clutch. Motor protection and soft start thanks to Intellitronics.

Technical data

		DKS15	DKS15L	DKS15S
Nominal power	W	2000	2000	2000
Output power	W	1340	1340	1340
Nominal speed	1/min	700/1700	540/1200	900/1700
Total length with spade handle	mm	510	510	510
Total length with pistol grip	mm	410	410	410
Weight	kg	5,8	5,8	5,8
Drilling diameter approx.				
rig operated (concrete)	mm	30-150	40-180	30-100
hand held (concrete)	mm	30-100	40-120	30-100
hand held (masonry)		30-180	40-200	30-120
Tool fixture		1 ¼“	1 ¼“	1 ¼“
Clamping neck diameter	mm	60	60	60
Suitable drill stand		KS18	KS18	KS18

Advantages

- Soft-impact function that can be switched on and off supports the motor and accelerates work progress
- Drill dust is removed from the diamond segments by soft impact and transported away by efficient dust extraction
- 2-speed dry drilling machine can be operated both by hand and in the drill stand
- Gearbox with oil bath lubrication and overload clutch
- Outstanding motor and gearbox efficiency guarantee exceptional drilling performance
- Leveling aid with two integrated spirit levels
- Centering spike for safe drilling (optional)
- Soft start and motor protection thanks to Intellitronics
- Compact size
- Low weight
- Available in various speeds
- Available with spade or pistol grip
- Supplied with tool set in a practical carrying case

Application examples

- Dry drilling of penetrations in concrete, masonry, and stone for cables, conduits, and pipes.
- Dry drilling in sensitive areas where water cannot be used for drilling.
- Perforation drilling for installations in sanitary and heating systems.
- Drilling of ventilation and air extraction openings.

Accessories

DK13240	Adaptor sleeve 1 ¼“ to G ½“

Details





WEKA Elektrowerkzeuge KG
Auf der Höhe 20
75387 Neubulach

Kontakt
Telefon: +49 7053 96816-0
Email: weka@weka-elektrowerkzeuge.de